

CHROMA AUSTRALIA PTY LTD ACN 001 594 609
17 Mundowi Rd / PO Box 3B
Mount Kuring-Gai, NSW 2080 AUSTRALIA
www.chromaonline.com
PH: (02) 9457 9922 FAX: (02) 9457 8082
EMERGENCY PH: As above, or Poisons Information Centre

Date of publication: 27th November 2013



Material Safety Data Sheet

Classified as **NON-HAZARDOUS** according to the criteria of Safe Work Australia (formerly ASCC – Australian Safety & Compensation Council [formerly NOHSC – National Occupational Health & Safety Commission])

IDENTIFICATION

Product name: Atelier Interactive™ Artists' Acrylic Paint

Other names: ----

Manufacturer's Product Codes: Various

Use: Professional artists' acrylic paint with extended drying time.

™ *Trademark of Chroma Australia Pty Ltd or an affiliated company

U.N. No: N/A

Hazchem: N/A

Dangerous Goods Class & Sub Risk: N/A

Poisons Schedule: N/A

PHYSICAL DESCRIPTION / PROPERTIES

Appearance: Thick paste, various colours

Boiling Point/Melting Point (°C): N/A

Vapour Pressure (pascals or mm of Hg at 25°C): N/A

Specific Gravity: Approx 1g/ml

Flash Point (°C): N/A

Flammability limits (%): N/A

Solubility in Water (g/L): Soluble

Other properties: N/A

COMPONENTS

Chemical Entity	CAS No.	Concentration
Pigments, varied	N/A	Commercial In Confidence
Acrylic polymers	Commercial In Confidence	Commercial In Confidence
Water	7732-18-5	<30%
Filler	1317-65-3	12.5 - 25%
Thickener	N/A	4 - 7.5%
Propylene Glycol	57-55-6	3%
PH Stabiliser	124-68-5	1.25 - 4%
Dispersant	N/A	Commercial In Confidence
Defoamer	265-155-0	0.25 - 0.5%
Surfactant	N/A	0.125 - 1.25%
Preservatives	26530-20-1, 2682-20-4, 2634-33-5	0.045%

NOTE: The physical data presented above are typical values only and should not be construed as a specification.

HEALTH HAZARD / TOXICOLOGICAL INFORMATION

No adverse health effects are expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms of effects may occur if the product is mishandled.

Inhalation: Inhalation of concentrated vapour may cause slight irritation

Ingestion: No adverse effects expected.

Eye Contact: Direct eye contact may cause slight irritation, redness and/or swelling.

Skin Contact: Prolonged or repeated contact may cause irritation.

Toxicological Data

This product carries the A.P. Non-Toxic Seal and is certified by a toxicologist in association with the Art & Craft Materials Institute (ACMI), Boston MA 02110 USA

FIRST AID MEASURES

Ingestion: Have affected person drink two (2) glasses of water. Never give anything by mouth to an unconscious person.

Inhalation: Inhalation of vapour may cause irritation; Move to fresh air. If irritation persists, consult a physician.

Skin contact: Prolonged or repeated contact may cause skin irritation; Wash affected areas thoroughly with cool water. If irritation persists, consult a physician.

Eye contact: Direct eye contact may cause irritation; Flush eyes with large amounts of cool water. If irritation persists, consult a specialist.

Advice to doctor: Treat symptomatically.

PRECAUTIONS FOR USE

Exposure limit(s): No Occupational Exposure Limits (OEL) value has been assigned.

Exposure controls

Engineering measures: Ensure adequate natural or mechanical ventilations. Keep containers closed when not in use.

Protective measures: Facilities storing or utilizing this material should be equipped with water facilities and appropriate ventilation equipment.

Individual protection measures

For general use Personal Protection Equipment (PPE) is not required; however a detailed risk assessment on the use of this product taking in to account the work environment and handling methods may indicate PPE is recommended.

Eye/face protection: General type safety goggles may be worn.

Skin protection: Single use nitrile gloves may be worn. Wash material immediately off skin with cool soapy water.

Respiratory protection: Not necessary if used in a ventilated environment

SAFE HANDLING & TRANSPORT INFORMATION

Safe handling: Avoid contact with eyes. Wash hands with cool soapy water after use. Personal clothing protection is recommended.

Storage: Keep from freezing. Store in a cool, dry place away from direct sunlight. Shake/stir well before use. Ensure lid is tightly closed when not in use.

Ambient storage temperature: 1°C - 38°C

Australian Dangerous Goods (ADG) Code: Not regulated (not dangerous for transport)

Classification for sea transport (IMO-IMDG): Not regulated (not dangerous for transport)

Classification for air transport (IATA/ICAO): Not regulated (not dangerous for transport)

Hazchem Code: None allocated

FIRE / EXPLOSION HAZARD

Flammability: Non-flammable

Suitable extinguishing equipment: Use extinguishing media appropriate to surrounding fire conditions.

Specific hazards during fire fighting: Material can boil above 100°C/212°F.

Special protective equipment for fire fighters: Wear self-contained breathing apparatus and protective clothing.

DISPOSAL ADVICE

Small quantities

Do not pour left over product into drains. Unwanted product should be brushed onto newspaper and allowed to dry to be disposed of via domestic waste collection. Soak/Wipe up smaller spills with a rag and dispose of via domestic waste collection.

Large quantities

Clean up immediately. Prevent spill and cleaning runoff from entering sewers, drains and open bodies of water. Contain spill with sand or other inert material and transfer to containers for disposal. Avoid walking through spilled product as it may be slippery. Contact local waste disposal authority for disposal advice.

OTHER INFORMATION

Allergy information: Due care has been taken to ensure this product does not contain any food derivatives or food-based products however we cannot guarantee the same applies to any of our suppliers of the individual components of this product.

Revision: 27th November 2013 – MSDS reformatted and extra information added.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates to only the specific material designated and may not be valid for such material when used in combination with any other materials or in any process unless specified in the text. Since Chroma Australia Pty Ltd cannot anticipate or control conditions of use, each user prior to using the product should assess and control the risks arising from usage of the product.