

CHROMA AUSTRALIA PTY LTD ACN 001 594 609
17 Mundowi Rd / PO Box 3B
Mount Kuring-Gai, NSW 2080 AUSTRALIA
www.chromaonline.com
PH: (02) 9457 9922 FAX: (02) 9457 8082
EMERGENCY PH: As above, or Poisons Information Centre

Date of publication: 27th November 2015



Material Safety Data Sheet

Classified as **HAZARDOUS** according to the criteria of Safe Work Australia (formerly ASCC – Australian Safety & Compensation Council [formerly NOHSC – National Occupational Health & Safety Commission])

Xn: Harmful, Danger - Aspiration Hazard Category 1



IDENTIFICATION

Product name: Archival Oils™ Odourless Solvent

Other names: ----

U.N. No: N/A

Hazchem: N/A

Dangerous Goods Class & Sub Risk: N/A

Poisons Schedule: 5

Manufacturer's Product Codes: AR71300, AR71330, AR71360, AR71390 & AR71420

Use: Low odour mineral turpentine substitute for thinning paints and cleaning brushes.

™ *Trademark of Chroma Australia Pty Ltd or an affiliated company

PHYSICAL DESCRIPTION / PROPERTIES

Appearance: Clear liquid

Flash Point: 75°C (Close Cup 80)

Boiling Point: 218 - 257°C

Explosive Limits (in air): 0.5 - 4.9

Vapour Pressure (mm of Hg at 20°C): 0.01

Vapour Density: @ 25°C – 2.43 mm²/s, @ 40°C – 1.89mm²/s

Odour: Isoparaffinic odour

Auto-Ignition Temperature: 250°C

Melting Point: -57.22°C

Molecular Weight: 195

Density @ 15°C: 0.792 kg/m³

Solubility in Water (g/L): <0.10

COMPONENTS

Chemical Entity	CAS No.	Concentration
Petroleum-Derived Complex Substance (Solvent)	64742-47-8	Commercial In Confidence

NOTE: The physical data presented above are typical values only and should not be construed as a specification.

HEALTH HAZARD / TOXICOLOGICAL INFORMATION

No adverse health effects are expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms of effects may occur if the product is mishandled.

Inhalation: Vapour concentrations above recommended exposure levels may be an irritation to the eyes and the respiratory tract, may cause headaches and dizziness, may act as an anaesthetic and may have other central nervous system effects.

Ingestion: Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema.

Eye Contact: Contact with eye will cause discomfort, but will not injure eye tissue.

Skin Contact: Frequent or prolonged contact may defat and dry the skin, leading to discomfort and

irritant dermatitis.

Toxicity Data

Mildly toxic – Inhalation of vapour concentrations above the Time Weighted Average (TWA) Value for Petroleum Derived Complex Substance may be irritating to the eyes and respiratory tract; may cause headaches and dizziness; may act as an anaesthetic and may have other effects on the central nervous system.

FIRST AID MEASURES

Ingestion: DO NOT induce vomiting. Administer artificial respiration if breathing is stopped. Keep at rest. Call for immediate medical attention.

Inhalation: Using proper respiratory protection, immediately remove the victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.

Skin contact: Flush with large amounts of water, use mild soap if available. Remove grossly contaminated clothing, including shoes, and launder before re-use.

Eye contact: Direct eye contact may cause irritation; Flush eyes with large amounts of cool water until irritation subsides. If irritation persists, consult a specialist.

Advice to doctor: Treat symptomatically. Avoid gastric lavage – aspiration of product into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema

PRECAUTIONS FOR USE

Exposure limit(s): No Time Weighted Average (TWA) exposure standard has been established for this product, however for Petroleum Derived Complex Substance the TWA = 1200mg/m³ (152 ppm) [ExxonMobil (2000)]

NB: The Time Weighted Average (TWA) value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week.

Exposure controls

Engineering measures: The use of mechanical or natural ventilation is recommended whenever this product is used in a confined space or is heated above ambient temperatures.

Protective measures: Facilities storing or utilizing this material should be equipped with water facilities and appropriate ventilation equipment.

Individual protection measures

For general use Personal Protection Equipment (PPE) is not required; however a detailed risk assessment on the use of this product taking in to account the work environment and handling methods may indicate PPE is recommended.

Eye/face protection: Safety goggles with side shields may be used.

Skin protection: Single use nitrile gloves may be worn. Wash material immediately off skin with cool soapy water.

Respiratory protection: Where concentrations in the air may exceed the TWA, it is recommended to use a half-face filter mask to protect from overexposure by inhalation. Suitable filter material depends on the workplace but a filter of material type “A” or similar may be considered for use.

SAFE HANDLING & STORAGE INFORMATION

Safe handling: Avoid contact with eyes. Wash hands with cool soapy water immediately after use. Personal clothing protection is recommended. Operation of use should be conducted in a well ventilated area using the smallest quantity possible.

Storage: Keep from freezing. Store in a cool, dry place, well ventilated away from direct sunlight and all sources of ignition. Shake/stir well before use. Ensure lid is tightly closed when not in use.

Ambient storage temperature: 1°C - 38°C

TRANSPORT INFORMATION

Classified as **NOT HAZARDOUS** for transport according to the criteria of Australian Dangerous Goods (ADG)Code

Classification for Australian land transport (ADG)

Proper Shipping Name:	PETROLEUM DERIVED COMPLEX SUBSTANCE
Class/Pack Group:	N/A
Special Precaution for User:	HARMFUL
UN Number:	N/A
Hazchem:	N/A

Classification for sea transport (IMO-IMDG):

Proper Shipping Name:	PETROLEUM DERIVED COMPLEX SUBSTANCE
Class/Pack Group:	N/A
Special Precaution for User:	HARMFUL
UN Number:	N/A
Hazchem:	N/A
Marine Pollutant:	No

Classification for air transport (IATA/ICAO):

Proper Shipping Name:	PETROLEUM DERIVED COMPLEX SUBSTANCE
Class/Pack Group:	N/A
Special Precaution for User:	HARMFUL
UN Number:	N/A
Hazchem:	N/A

REGULATORY INFORMATION

Poisons Schedule:	5
AICS Name:	Distillates, Petroleum, Hydrotreated Light
NZ Toxic Substance:	4
EPG:	N/A

FIRE / EXPLOSION HAZARD

Hazchem Code: None allocated

Suitable extinguishing equipment

Stable. Use foam, dry chemical, or water spray to extinguish fire.

Specific hazards during fire fighting

Combustible liquid; low hazard. Material can form a flammable mixture or can burn only upon heating to temperatures at or above the flash point of 75°C.

Special protective equipment for fire fighters

Wear self-contained breathing apparatus and full protective clothing. Use water spray to cool fire exposed surfaces. Use foam, dry chemical, or water spray to extinguish surrounding fire.

DISPOSAL / ACCIDENTAL RELEASE ADVICE**Small quantities**

Do not pour left over product into drains. Unwanted product should be brushed onto newspaper and allowed to dry to be disposed of via domestic waste collection. Soak/Wipe up smaller spills with a rag and dispose of via domestic waste collection.

Large quantities

Clean up immediately. Prevent spill and cleaning runoff from entering sewers, drains and open bodies of water. If a large amount of product enters a waterway advise your local Waste Management. Contain spill with sand or other inert material and transfer to containers for disposal. Avoid walking through spilled product as it may be slippery. Contact local waste disposal authority for disposal advice.

OTHER INFORMATION

Allergy information: Due care has been taken to ensure this product does not contain any food derivatives or food-based products however we cannot guarantee the same applies to any of our suppliers of the individual components of this product.

Revision: 14th January 2014 – MSDS reformatted and extra information added.
27th November 2015 – MSDS renewed and GHS Pictogram added.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates to only the specific material designated and may not be valid for such material when used in combination with any other materials or in any process unless specified in the text. Since Chroma Australia Pty Ltd cannot anticipate or control conditions of use, each user prior to using the product should assess and control the risks arising from usage of the product.